

TS-6P




RoHS COMPLIANCE



Features


- ◇ UL Recognized File # E-326243
- ◇ Glass passivated junction
- ◇ Ideal for printed circuit board
- ◇ High case dielectric strength of 2000V_{RMS}
- ◇ Plastic material has Underwriters Laboratory Flammability Classification 94V-0
- ◇ Typical IR less than 0.1uA
- ◇ High surge current capability to 240A
- ◇ High temperature soldering guaranteed: 260 °C / 10 seconds at 5 lbs., (2.3kg) tension
- ◇ Green compound with suffix "G" on packing code & prefix "G" on datecode.



Mechanical Data

- ◇ Case: Molded plastic body
- ◇ Terminals: Pure tin plated, Lead free. Leads solderable per MIL-STD-202, Method 208
- ◇ Weight: 7.15 grams
- ◇ Mounting torque : 8.17 in. lbs. Max.

Dimensions in inches and (millimeters)



Marking Diagram

- TS15P0XG = Specific Device Code
- G = Green Compound
- Y = Year
- WW = Work Week

Maximum Ratings and Electrical Characteristics

Rating at 25 °C ambient temperature unless otherwise specified.

Single phase, half wave, 60 Hz, resistive or inductive load.

For capacitive load, derate current by 20%

Type Number	Symbol	TS15P 01G	TS15P 02G	TS15P 03G	TS15P 04G	TS15P 05G	TS15P 06G	TS15P 07G	Units
Maximum Recurrent Peak Reverse Voltage	V _{RRM}	50	100	200	400	600	800	1000	V
Maximum RMS Voltage	V _{RMS}	35	70	140	280	420	560	700	V
Maximum DC Blocking Voltage	V _{DC}	50	100	200	400	600	800	1000	V
Maximum Average Forward Rectified Current @T _C =110°C	I _{F(AV)}	15							A
Peak Forward Surge Current, 8.3 ms Single Half Sine-wave Superimposed on Rated Load (JEDEC method)	I _{FSM}	240							A
Rating of fusing (t < 8.3mS)	I ² t	239							A ² S
Maximum Instantaneous Forward Voltage (Note 1) @ 7.5A @ 15A	V _F	1.0 1.1							V
Maximum DC Reverse Current @ T _A =25 °C at Rated DC Blocking Voltage @T _A =125 °C	I _R	10 500							uA uA
Typical Junction Capacitance Per Leg (Note 2)	C _j	90							pF
Typical Thermal Resistance	R _{θJC}	0.8							°C/W
Operating Temperature Range	T _J	- 55 to + 150							°C
Storage Temperature Range	T _{STG}	- 55 to + 150							°C

Note 1 : Pulse Test with PW=300 usec, 1% Duty Cycle

Note 2 : Measured at 1MHz and applied Reverse bias of 4.0V DC.

RATINGS AND CHARACTERISTIC CURVES (TS15P01G THRU TS15P07G)

FIG. 1 MAXIMUM SURGE CURRENT PER LEG




FIG. 2 TYPICAL FORWARD CHARACTERISTICS PER LEG




FIG. 3 MAXIMUM DERATING CURVE FOR OUTPUT CURRENT




FIG. 5 TYPICAL REVERSE CHARACTERISTICS PER LEG





FIG. 4 TYPICAL JUNCTION CAPACITANCE



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Taiwan Semiconductor:](#)

[TS15P01G](#) [TS15P02G](#) [TS15P03G](#) [TS15P04G](#) [TS15P05G](#) [TS15P06G](#) [TS15P07G](#)